

A4

PRIMO

Platform size 1600x1100 mm



KALEA 
LIFTS

NEXT LEVEL

KALEA A4 PRIMO - PLATFORM SIZE 1600 X 1100 MM

THE KALEA A4 PRIMO ASSORTMENT IS EXTENDED WITH YET ANOTHER SIZE - the platform size 1600 x 1100 mm.

KALEA A4 PRIMO is a screwdriven vertical platform lift with selfsupporting shaft enclosure. When other lift types need construction work, pit, machine and head room, the A4 PRIMO demands minimum space and effort. The lift is easy to install and is delivered with a prefabricated shaft made of steel or laminated safety glass panels.

Safety edges, emergency lighting and an alarm button guarantees that you feel completely safe. Personalize your Kalea A4 PRIMO by choosing your own colour, an elegant glazed shaft or the standard steel shaft in combination with a variety of accessories and options.

THE KALEA A4 PRIMO is EC-type tested and certified by the Notified Body DNV, Det Norske Veritas.

KALEA A4 PRIMO ASSORTMENT:

Platform sizes: 1500 x 1000 mm
 1500 x 1100 mm
1600 x 1100 mm NEW

TECHNICAL FACTS - KALEA A4 PRIMO 1600x1100 mm	
Rated load	500 kg
Rated speed	9 m/min (0,15 m/s)
Lifting height	Up to 13 meters
Platform dimensions	1600 x 1100 mm (depth x width, mm)
Footprint dimensions	1730 x 1500 (depth x width, mm)
Shaft	Steel panels painted in off white RAL 9016
Door configuration	Single-entry, open through (A & C-side)
Doors	Single hinged doors Standard steel door fronts painted off white RAL 9016 Aluminium door fronts in natural anodized aluminium Fire and gas resistant doors EI60
Door dimensions	2000 x 900 mm
Gate dimensions	1100 x 900 mm (lifting height < 3 m)
Control system	Micro computer based control system
Power supply	400 V, 3-phase 50/60 Hz, 16 A starting current Soft start and stop as option (380-400 V, 3-phase frequency converter)
Motor power	2,2 kW
Options	Telephones, locking systems, automatic door openers, elbow buttons, electric battery lowering, IR-control, automatic shaft lighting, arrival bells, level indicator, outdoor roof, door front cover etc.
KALEA A4 PRIMO is EC-type tested and certified by the Notified Body DNV and complies with the EC Standard EN 81-41.	



KALEA A4 PRIMO

- A variety of accessories and options
- Steel shaft as standard or glazed shaft as option
- Steel doors with panoramic window as standard
- Exclusive aluminium doors as option
- A variety of optional RAL colours

KALEA LIFTS AB

Office:
 Address: A Odhners Gata 17, 421 30 V Frölunda, Sweden
 Phone: +46 31 49 04 40
 Web: www.kalealifts.com

Office:
 Address: Hästhagsvägen 8, 194 52 Upplands-Väsby, Sweden
 Phone: +46 8 594 115 50
 Web: www.kalealifts.com